

IW25-4 IN Wall Dehumidifier

HumidityHappens.com

DIMENSIONS

IN Wall Base Unit	27.625" x 14.25" x 5.75"
IN Wall Unit/ Cover	30.375" x 17.25" x 7.25"
Rough Opening	28" x 14.5" x 5.75"
Exterior Sleeve	17.5" 30.5" x 2.2"

PERFORMANCE

Weight	39
Spaced For	1,500 sq ft
Rated Average Power Consumption	300 Watts @ 80°F/60% RH
Max Power Consumption	440 Watts @ 90°F/95% RH
Max Absorbed Current F.L.A.	2.8 Amps @ 80°F/60% RH
Locked Rotor Current L.R.A	14.5 Amps
Air Flow	155 cfm
Second Pressure Level	45 dBA
Functioning Temperature Range	46-95°F
Functioning Relative Humidity Range	34-95% RH
Rated Condensation Capacity	up to 29.5 PPD @ 80°F/60% RH
Warranty	5 Years on Parts & Labor

MATERIALS

Drain Connection Length	10'
Drain Connection Diameter	3/4" Hose
Refrigerant	R134A 190G

ELECTRICAL

Volt Frequency	120 VAC/ 60 Hz
Amp Draw	2.7 Amps

OPTIONAL ACCESSORIES

Condensate Pump
Exterior Sleeve

Remove Moisture • Prevent Mold

It's that Simple

IW25-4 IN Wall Dehumidifier

Reap the benefits of supplemental dehumidification in your multifamily properties with the versatile **IW-25-4 IN Wall Dehumidifier**. Designed to reduce mold and humidity by removing excess moisture in apartments. The ENERGY STAR® Certified, tankless, quiet, and stand-alone dehumidifier features an updated modern design. Additional features: the FIRST integrated condensate pump in a fixed dehumidifier (optional), recessed versatility in a 2x4 OR 2x6 wall - perfect for new construction, LED light for simplified maintenance, tamper-proof cover, 5-year warranty, and more! Innovative Dehumidifier Systems, LLC the pioneers of in-wall dehumidifiers.



IW25-4 IN Wall Dehumidifier Accessories

Exterior Sleeve (optional)

Exterior Sleeve Dimensions	17.5" 30.5" x 2.2"
Weight	5 lbs



CONDENSATE PUMP (optional)

Voltage	24 VDC
Max Flow	7 L/minute
Max Pump Lift	10'
Power Consumption	10 Watts
Revolving Speed	5,300 RPM
Drain Hose Diameter	1/4"
Drain Hose Length	21'

