

# IW25-4 ON Wall Dehumidifier

HumidityHappens.com

## DIMENSIONS

ON Wall Base Unit	27.625" x 14.25" x 5.75"
ON Wall Unit/ Cover	27.625" x 14.25" x 7.25"
Key Hole Mount Distance	6.2"

## PERFORMANCE

Weight	39
Spaced For	1,500 sq ft
Rated Average Power Consumption	300 Watts @ 80°F/60% RH
Max Power Consumption	440 Watts @ 90°F/95% RH
Max Absorbed Current F.L.A.	2.8 Amps @ 80°F/60% RH
Locked Rotor Current L.R.A	14.5 Amps
Air Flow	155 cfm
Second Pressure Level	45 dBA
Functioning Temperature Range	46-95°F
Functioning Relative Humidity Range	34-95% RH
Rated Condensation Capacity	up to 29.5 PPD @ 80°F/60% RH
Warranty	5 Years on Parts & Labor

## MATERIALS

Drain Connection Length	10'
Drain Connection Diameter	3/4" Hose
Refrigerant	R134A 190G

## ELECTRICAL

Volt Frequency	120 VAC/ 60 Hz
Amp Draw	2.7 Amps

## OPTIONAL ACESORY: CONDENSATE PUMP

Voltage	24 VDC
Max Flow	7 L/minute
Max Pump Lift	10'
Power Consumption	10 Watts
Revolving Speed	5,300 RPM
Drain Hose Diameter	1/4"
Drain Hose Length	21'



## Remove Moisture • Prevent Mold

It's that Simple

Reap the benefits of supplemental dehumidification in your multifamily properties with the versatile IW-25-4 ON Wall Dehumidifier. Designed to reduce mold and humidity by removing excess moisture in apartments. The ENERGY STAR® Certified, tankless, quiet, and stand-alone dehumidifier features an updated modern design.

