

IW25-4 DEHUMIDIFIER

INNOVATIVE INSTALLATIONS



2 X 6 IN Wall Installation

Recesses In Wall

IW25-4 IN Wall Dehumidifier fits directly in between interior studs and 2 x 6 wall without any overlap. The dehumidification system measures 5.75" in depth for simplified installation and clean finish. Only one side of wall will need to be cut for the rough opening. Ideal for new construction and applications with 2 x 6 wall framing.

Rough Opening Dimensions:
28" x 14 1/2" x 5 3/4"

2 x 6
WALL

POWER
SUPPLY

DRAIN
HOSE

2 x 4 IN Wall Installation

Recessed Fits Through Wall

The IW25-4 IN Wall Dehumidifier recesses directly through wall; There are no additional accessories needed for installation. Ideal for new construction when recessed installation is preferred.

Semi-Recessed Exterior Sleeve 2 x 4 Wall

The IW25-4 IN Wall Dehumidifier can be semi-recessed into the front side of wall with Exterior Sleeve for a clean bump out finish. Only one side of the wall will be cut for rough opening. Ideal for 2 x 4 applications with limited space to fully recess unit.

Rough Opening Dimensions:
28" x 14 1/2" x 5 3/4"

2 x 4
WALL

POWER
SUPPLY

DRAIN
HOSE

2 x 4
WALL

POWER
SUPPLY

DRAIN
HOSE

EXTERIOR
SLEEVE

Direct ON Wall Mount Installation



Mounts On Wall

IW25-4 ON Wall Dehumidifier hangs directly on wall. Depending on application, drain and electrical can be routed through alternate punch-out holes on frame of dehumidifier. No cuts needed to install the unit directly on wall. Ideal for existing properties. Provides opportunities for creative installations such as cabinets, kitchen islands, and hard surface walls.

DRAIN
HOSE

POWER
SUPPLY



IW25-4 DEHUMIDIFIER

INNOVATIVE INSTALLATIONS

Optional Installation Accessories



Integrated Condensate Pump Built for IW25-4

The Integrated Condensate Pump was designed for automatic collection and removal of condensate when gravity drainage is not possible or practical. The pump includes 10' lift that can continuously flow downhill with gravity, or 15' without downhill slope. Pump mounts directly **into** dehumidifier for tamper-proof control.

Dimensions:
7 1/8" x 3" x 2 3/4"



Exterior Sleeve

The Exterior Sleeve allows the IW25-4 IN Wall Dehumidifier to be semi-recessed into walls, closet, cabinets and other creative installations. The Exterior Sleeve includes punch-out holes on side and bottom for versatile drain hose and power routing. The Exterior Sleeve frames the dehumidifier for a clean fit and clean aesthetic.

Dimensions:
17 1/2" x 30 1/2" x 2 1/5"

IW25-4 IN Wall / ON Wall Dehumidifier Features:

- ENERGY STAR® Certified
- 5 Year Full Warranty on Parts and Labor
 - Runs independently of HVAC systems
 - Designed for quiet operation 45 dBA
 - Tamper-proof front cover
- Built-in humidistat concealed behind front cover
 - MERV 8 washable/ reusable filter
- Automatic restart in the event of power failure
 - Pulls up to 29 pints of water per day
 - LED light filter reminder
- Hard wire capable or connect to a standard 120V outlet with 10' power cord

