

## IW25-5 On-Wall Dehumidifier With Bi-Polar Ionizer Product Specifications

ON WALL DIMENSIONS		
On Wall Base Unit	27.625" x 14.25" x 5.75"	
On Wall Unit/Cover	27.625" x 14.24" x 7.25"	
Keyhole Mount Distance	3.125	
Weight	39 lbs	
OPERATIONAL PERFORMANCE		
	@ 80°F/60% RH	@ 65°F/60% RH
Water Removal	Up to 33 PPD	Up to 21 PPD
Energy Factor	1.65 L/kWh	1.92 L/kWh
Spaced For	1,500 sq. ft.	
Air Flow (with clean air filter)	120 CFM	
Sound Pressure Level	47 dBA	
Operating Temperature Range	46-95°F	
Functioning Relative Humidity Range	36-90%	
Warranty	5 Years on Parts & Labor	
Drain Connection Length	10'	
Drain Connection Diameter	¾" O.D.	
Refrigerant R32	155G	
ELECTRICAL		
Supply Voltage	120 VAC/60 Hz	
Rated Average Power Consumption	300 Watts @ 80°F/60% RH	
Max Power Consumption	440 Watts @ 90°F/95% RH	
Max Absorbed Current F.L.A.	2.8 Amps @ 80°F/60% RH	
Locked Rotor Current L.R.A.	14 Amps	
ION GENERATOR		
Ion Output	3,000,000/cc	
Test Condition	20Cm; Wind Speed 1m/s	
Ion Type	Bi-Polar/Positive and Negative Ions	
Input Voltage	DC 24. 0V±0.1V	

NOTE: Specifications subject to change without notice.

